

The Voce E2 is Teletechno functional IP phone for discerning and professional users with admirable design. The 4 SIP account and 3.2" 224 x 128 Pixel Grayscale LCD screen IP phone has been designed to be an indispensable terminal equipment of office communication for any size enterprise. With HD voice quality and enhanced speaker box, it enable a high quality voice experience and all calls on it will be more like a face-to-face communication.



- Elegant appearance
- Full HD Audio (handset, speaker, ringtone)
- 3.2" 224 x 128-pixel LCD display with backlit
- Up to 4 SIP Account
- PoE Support
- WiFi Connection (Optional)
- Support up to 5x Expansion Module



Elegant Appearance

Desktop phone is a product you have with you all the time at office, Teletechno not just made a new phone, but wants to deliver a much better phone. Each tiniest detail about Voce E2 phone has been designed by a lot of good ideals, include the construct of keys, handset, foot stand etc. And all material is made with the remarkable precision, to ensure it's suitable for your office decoration style.



Life-like Voice Quality

The Voce E2 is built for very highest level voice performance. It supports G.722 codec, which covers a wide range including both low frequency and high frequency bands, and it complies with TIA920 certification standards, enable calls with a HD voice quality just like you're face to face communicating with the other party. Furthermore, the Voce E2 has been the first IP phone that support full HD, such HD handset, HD speaker, and HD ring tones.



Easy Configuration

The Voce E2 is supported Auto Provisioning by TFTP / FTP / HTTP / PnP, which make installer configure and maintain all phones easier and more convenient.



Compatibility

The Voce E2 Validated by Elastix and Broadsoft, to ensure an outstanding compatibility with leading VoIP platforms.



Advanced Connectivity and Expandability

You're able to connect Voce E2 with LAN network by PoE technology (IEEE 802.3af Power over Ethernet) or WiFi technology (Optional), to clean redundant wires from your office table.

Display Features

LCD Display: 224x128 dot-matrix, 4-level gray scale
FSTN LCD
LCD Size:.3.2
LCD Comtrast:Adjustable
LCD Backlight:Adjustable

Install Option

Desk Mount:Yes
Wall Mount:Yes

Network Features

IP Version:IPv4
IP Assignment:Yes (Static / DHCP / PPPoE)
WiFi Connection:Optional
DNS:Yes (Primary and Secondary DNS supported)
HTTP:Yes
SNTP Client:Yes
VLAN (802.1Q):Yes
QoS (DiffServ):Yes
VPN:Yes (L2TP VPN supported)
NAT Transverse:Yes (STUN mode)
Security:Yes (SRTP / TLS supported)

Others

Power Consumption:
Standby:1.0W,
Working:2.2W
Operating Humidity:10 - 90%
Operating Environment:0°C - 45°C (32°F - 113°F)
Dimension (W x D x H):
218 x 176 x 129mm
Weight:1.3Kg

SIP Features

SIP Accounts:4
SIP Compatibility:SIP v1 (RFC2543), v2 (RFC3261), Asterisk,Broadsof

Keys Features

Programmable Keys:8
Features Keys:7 (Menu, Hold, Redial, Mute, Headset, hands-free speakerphone, Message)
Line LED Keys:4
Volume Control Keys:2
Context Sensitive Soft Keys:4
Navigation Keys:4

Configuration

Plug & Play Configuration:Server based configuration
Manual Configuration:Internal Web Configurator, Local (LCD based) network Configuration
Auto Provision:TFTP / FTP / HTTP / PnP

Interface Features

Ethernet Ports:2x 10 / 100 Mbps
RJ45 Expansion Module Port:
1 (Up to 2x LCD Expansion Modules)
PoE (Power over Ethernet):IEEE 802.3af Class 2 standard compliant
Headset Jack:1x RJ9
Handset Jack:1x RJ9
Power adapter Jack:3.5mm,DC 5.0V, 1.0A

Audio Features

Handset,Speaker,Headset Volume
Ringtones:10+2 user define
Ringer Volume:8 levels + off
Audio Codec:G.711(A/μ),G.722 (Wideband),L16 PCM (Wideband), G.726,G.729AB,iLBC

Software Features

Phone Book (Entries):200
Call Log Entries:200 Incoming calls + 200 Outgoing Calls +200 Missed calls
Conferencing:3 parties
Music On Hold:Supplied by Host Service (PBX/SIP Server)

Phone Basic Functions: One-Touch, Speed Dial, Redial,Call Forward, Call Waiting,Call Transfer,Call Hold, Call Return,Mute, Auto answer, DND, Call History: Dialed /Received/Missed, Direct IP Call without SIP Proxy, Hotline, Dail Plan,Set Date/Time Manually or Automatically

Phone Functions with IP PBX:
Anonymous Call, Anonymous Call Rejection, DND & Forward, Synchronization Message Waiting Indicator (MWI), Voice Mail, Call Park, Call Pickup Intercom, Paging, Music on Hold ,Call Recording